

## LED T8 Tubes

Highborn LED has the latest in LED T8 tube technology, available for commercial fluorescent tube replacement. By replacing existing fluorescent tubes with one our LED T8 tubes, you can reduce your energy costs by 50%. Save money by replacing the bulb versus replacing the entire fixture. This LED T8 tube is mercury-free and therefore environmentally friendly. For cost-efficient, eco-friendly lighting solutions, Highborn LED provides superior LED replacement lamps with a long life span. All of our 4 ft. LED T8 tubes are UL- and/or DLC-listed/LDL-listed. These products are eligible for rebate with most major power companies.



LED T8 Tubes

# Specifications



Item#/SKU	Power	Size	Lumens	Color Temperature	Style	Connector	Input Voltage	Operating Temperature	Beam Angle	Lifespan
102657	9W	2 ft, 2-pin	1035	6500K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102467	18W	4 ft, 2-pin	1800	5000K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102467-1	18W	4 ft, 2-pin	1800	5000K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102467-2	18W	4 ft, 2-pin	1800	4000K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102467-3	18W	4 ft, 2-pin	1800	4000K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102467-4	18W	4 ft, 2-pin	1800	3500K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102467-5	18W	4 ft, 2-pin	1800	3500K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102442	20W	4 ft, 2-pin	2000	5000K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102442-1	20W	4 ft, 2-pin	2000	5000K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102442-2	20W	4 ft, 2-pin	2000	4000K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102442-3	20W	4 ft, 2-pin	2000	4000K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102442-4	20W	4 ft, 2-pin	2000	3500K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102442-5	20W	4 ft, 2-pin	2000	3500K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102426	22W	4 ft, 2-pin	2200	5000K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102426-1	22W	4 ft, 2-pin	2200	5000K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102426-2	22W	4 ft, 2-pin	2200	4000K	Frosted	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102426-3	22W	4 ft, 2-pin	2200	4000K	Clear	1 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102426-4	22W	4 ft, 2-pin	2420	6500K	Clear	2 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
102426-5	22W	4 ft, 2-pin	2420	6500K	Frosted	2 Side	85-277V	-4°F/104°F	120°-150°	80,000 hrs
101261	44W	8 ft, 1-pin	4840	6500K	Clear	2 Side	100-277V	-4°F/104°F	120°-150°	80,000 hrs
101261-1	44W	8 ft, 1-pin	4840	6500K	Special	2 Side	100-277V	-4°F/104°F	120°-150°	80,000 hrs